# Yuasa Technical Data Sheet

### Yuasa NP1.2-12 Industrial VRLA Battery

<b>Specifications</b> Nominal voltage (V) 20-hr rate capacity to 1.75v per cell at 20°C (Ah) 10-hr rate Capacity to 1.8V/Cell at 20°C (Ah) 20-hr rate Capacity to 1.75V/Cell at 20°C (Ah)	12 1.2 1.1 1.2
<b>Dimensions</b> Length (mm) Width (mm) Height over terminals (mm) Mass (kg)	97 (±1) 48 (±1) 54.5 (±2) 0.58
<b>Terminal Type</b> FASTON - Quickfit / release (JST where stated)	4.75
<b>Operating Temperature Range</b> Storage (in fully charged condition) Charge Discharge	-20°C to +60°C -15°C to +50°C -20°C to +60°C
<b>Storage</b> Capacity loss per month at 20°C (% approx.)	3
<b>Case Material</b> Standard	ABS (UL94:HB)
<b>Charge Voltage</b> Float charge voltage at 20°C (V)/Block Float charge voltage at 20°C (V)/Cell Float Chg voltage tmp correction factor from std 20°C (mV)	13.65 (±1%) 2.275 (±1%) -3
Cyclic (or Boost) charge Voltage at 20°C (V)/Block Cyclic (or Boost) charge Voltage at 20°C (V)/Cell Cyclic Chg voltage tmp correction factor from std 20°C (mV)	14.5 (±3%) 2.42 (±3%) -4
<b>Charge Current</b> Float charge current limit (A) Cyclic (or Boost) charge current limit (A)	No limit 0.3
<b>Maximum Discharge Current</b> 1 second (A) 1 minute (A)	36 12
Impedance	





### Layout

Θ	
$\oplus$	

# 3rd Party Certifications

ISO9001 - Quality Management Systems



# Safety

110

3 to 5 years

up to 5

#### Installation

Can be installed and operated in any orientation except permanently inverted.

## Handles

Batteries must not be suspended by their handles (where fitted).

#### Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

## Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

#### Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.



Data Sheet generated on 29/08/2023 – E&OE

EUROBAT Classification: Standard Commercial

Measured at 1 kHz (mΩ) Design Life & Approvals

Yuasa design life at 20°C (yrs)

The world's leading battery manufacturer

www.yuasaeurope.com

