

# SL-760 Size: AA

> iXtra – long term high performance


### Performance Data

(Typical values for batteries stored at +25 °C for one year)


System	Lithium Thionyl Chloride
Nominal voltage	3.6 V
Nominal capacity	2.2 Ah
Nominal current	2 mA
Max. continuous discharge current	100 mA
Pulse current capability	200 mA
Anode surface area	14 cm <sup>2</sup>
Lithium content	0.65 g
Weight	18 g
Volume	8 cm <sup>3</sup>
Temperature range	-55 °C ... +85 °C




SL-760/S




SL-760/T




SL-760/P



SL-760/PR



SL-760/PT




### Available Terminations

Termination	Catalogue No.
SL-760/S Standard	11 1 07601 00
SL-760/T Tags	11 1 07602 00
SL-760/P Pins	11 1 07603 00
SL-760/PR Pins radial	11 1 07606 00
SL-760/PT Polarized tags	11 1 07608 00


### Catalogue No.

**WARNING:**  
Fire, explosion, and severe burn hazard. Do not recharge, disassemble, heat above 100 °C, incinerate, or expose contents to water.


### Typical Discharge Curves at +25 °C



### Available Capacity



### Operating Voltage



### Voltage Response at +25 °C, Pulse: 20 mA

